

PATENT APPLICATION

PARALLEL ALIGNMENT METHOD AND APPARATUS FOR CHEMICAL MECHANICAL POLISHING

Inventor: Thomas Walsh
805 Spring Creek Way
Templeton, CA 93465.
Citizen of United States of America

Assignee: LAM RESEARCH CORPORATION
4650 Cushing Parkway
Fremont, California 94538

MARTINE & PENILLA, LLP
710 Lakeway Drive, Suite 170
Sunnyvale, California 94085
Telephone (408) 749-6900
Customer No. 25920

5

PARALLEL ALIGNMENT METHOD AND APPARATUS FOR CHEMICAL MECHANICAL POLISHING

CROSS REFERENCE TO RELATED APPLICATIONS

10

This application is a continuation of U.S. Patent Application No. 09/038,875, filed on March 11, 1998, and entitled "PARALLEL ALIGNMENT METHOD AND APPARATUS FOR CHEMICAL MECHANICAL POLISHING," which is incorporated herein by reference in its entirety. This application is also a continuation-in-part of U.S. Patent Application No. 08/892,795, filed on July 15, 1997 issued on April 4, 2001 as U.S. Patent 6,045,716, and entitled "CHEMICAL MECHANICAL POLISHING APPARATUS AND METHOD", which claims priority to a U.S. Provisional Application No. 60,036,298, filed on March 12, 1997, the disclosures of which are incorporated herein by reference in their entirety.

20

BACKGROUND OF THE INVENTION

25

The present invention relates to the manufacture of integrated circuits. More particularly, the invention provides a technique including a method and an apparatus for chemical mechanical polishing using a device that maintains substantially parallel alignment between a surface of a film being polished and a rotating polishing surface, as well as other features. Among other benefits, parallel alignment tends to produce more uniformity in the film being processed and maintains film quality.

30

Chemical mechanical polishing or planarization ("CMP") is a technique of polishing materials including semiconductor substrates and films overlying such substrates, which provides a high degree of uniformity and planarity. The process is used to remove high elevation features on films created during the fabrication of a microelectronic circuitry on the substrate, or to remove a layer of film to reveal the

5 circuitry buried underneath the film. In some cases, the process can even planarize semiconductor slices prior to the fabrication of microelectronic circuitry thereon.

10 A conventional chemical mechanical polishing process uses an apparatus having a single large polishing pad positioned on a platen, against which a substrate is positioned for polishing. A positioning member positions and biases the substrate to be polished against the polishing pad, which is rotating. A chemical slurry, which is likely to have abrasive materials, is maintained on the polishing pad to modify the polishing characteristics of the polishing pad and to enhance the polishing of the substrate or films.

15 Unfortunately, chemical mechanical polishing is not free from limitations in the manufacture of integrated circuits. For instance, CMP is extremely time consuming, which generally influences wafer throughput. Additionally, the polishing pad often accumulates residual by-products from the polishing operation or wears and deforms the polishing pad, which leads to degradation of the polishing efficiency for the polishing operation. Furthermore, the apparatus with the single
20 polishing pad can only perform a single process such as dielectric layer polishing or tungsten film polishing, thereby requiring an additional apparatus to perform other processes. Moreover, conventional CMP of large substrate surfaces tends to be problematic, since it is often difficult to maintain parallel alignment between a substrate
25 surface and a rotating polishing surface using conventional techniques. Accordingly, conventional chemical mechanical polishing has a variety of limitations.

From the above, it is seen that a technique for chemical mechanical polishing which is cost effective and efficient is often desirable.

SUMMARY OF THE INVENTION

According to the present invention, an improved technique for chemical mechanical polishing is provided. In particular, the technique uses an apparatus having a multi-head turret for providing chemical mechanical polishing using one of a plurality of polishing surfaces. In an exemplary embodiment, each of the carrier devices, which secures a workpiece to be processed, is coupled to a common turret by way of at least two fingers that are pivotable to secure each carrier device in parallel alignment to one of a plurality of the polishing surfaces. These two fingers that are pivotable absorb process non-uniformities to maintain parallel alignment between a surface of the workpiece and the polishing surfaces.

In a specific embodiment, the present invention provides an apparatus for chemical mechanical polishing using a plurality of carrier devices rotatably coupled to a turret. The apparatus includes the turret and a plurality of rotatable polishing surfaces (e.g., rotating polishing pad and platen) positioned around the turret. The apparatus also includes a plurality of carrier devices and rotatably coupled to the turret, where the carrier devices are each adapted to hold a workpiece (e.g., a wafer, a semiconductor wafer, a patterned semiconductor wafer, a plate, hard drives, a display panel, a substrate, and magneto resistive read-write heads) to be polished on at least one of the rotatable polishing surfaces. Each of the carrier devices is operably independent to each other during a process for chemical mechanical polishing. Accordingly, each of the carrier devices can move freely in three dimensions, e.g., vertical, radial, and angular, i.e., rotational or tangential. In preferred embodiments, each of the carrier devices, which secures a workpiece, is coupled to a common turret by way of at least two fingers that secure each carrier device in parallel alignment to one of a plurality of the polishing surfaces. Parallel alignment is maintained over any substantial variations in processing conditions.

In an alternative embodiment, the present invention provides a method of processing a surface of a workpiece using, for example, an apparatus for chemical

5 mechanical polishing. The method includes steps such as securing a workpiece onto a carrier device, where the film to be processed faces away from the carrier device. The method positions a surface of the workpiece against a rotatable polishing surface, which biases the face against the rotatable polishing surface. In a specific embodiment, the workpiece is rotating and the rotatable polishing surface is also rotating as the face is
10 biased. The method also includes a step of maintaining a substantially planar or parallel configuration between the surface of the workpiece and the rotatable polishing surface. Such maintaining step occurs by at least two fingers or pivotable members operable coupled to the spindle of the carrier device. In operation, the two fingers are in a substantial parallel alignment position relative to each other, which keeps the
15 spindle in a substantial normal position relative to the surface of the workpiece. Variations in a process that cause the spindle to move out of a normal position can be absorbed by the two fingers or pivotable members, which couple to the fingers by movable couplings. Parallel alignment is maintained over any substantial variations in processing conditions.

20 Benefits are achieved using the present invention. In particular, the multi-carrier design allows for higher wafer throughput over pre-existing techniques. Additionally, a variety of polishing processes (or recipes) can be performed using the present apparatus. Furthermore, each of the carriers can be adjusted in two or three dimensions independent of each other to achieve desired processing conditions.
25 Additionally, the use of more than one finger coupled to a carrier device maintains a surface of a workpiece secured by the carrier device in substantially parallel alignment to a rotating polishing surface, which provides for a more uniform and accurate polishing process. These and other benefits are described throughout the present specification, and more particularly below.

30

The present invention achieves these benefits in the context of known process technology. However, a further understanding of the nature and advantages of the present invention may be realized by reference to the latter portions of the specification and attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a simplified top-view diagram of a CMP apparatus according to the present invention;

10 Figure 1A is a more detailed top-view diagram of a turret assembly for the CMP apparatus of Figure 1 according to the present invention;

Figure 2 is a simplified side-view diagram of polishing tables for the CMP apparatus of Figure 1 according to the present invention;

Figure 3 is a simplified side-view diagram of carrier devices for the CMP apparatus of Figure 1 according to the present invention;

15 Figures 3A and 3B show simplified diagrams of carrier devices for the CMP apparatus of Figure 1 according to the present invention;

Figure 4 is a simplified flow diagram of a method according to the present invention; and

20 Figure 5 is a simplified flow diagram of an alternative method according to the present invention.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

The present invention provides a technique including a method and an apparatus for performing CMP or the like. In preferred embodiments, the present invention provides a CMP apparatus having one or more carrier devices, which secures a workpiece. Each carrier device is coupled to a common turret by way of at least two fingers that secure each carrier device in parallel alignment to one of a plurality of the polishing surfaces. The combination of the fingers and the carrier device in a novel configuration provides for more uniform and accurate processing of, for example, a film or films on semiconductor wafers and the like.

15

Figure 1 is a simplified top-view diagram of a CMP apparatus 100 according to the present invention. This diagram is merely an illustration and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize other variations, alternatives, and modifications. To assist the reader in understanding the various features of the present invention, a spatial coordinate system is defined on the CMP apparatus. As shown, a vertical axis is defined by reference letter "z," which protrudes upwardly from and along the center region of the turret in an axial manner. A radial axis is defined by reference letter "r," which protrudes radially from the center region. Also shown is "r'," which defines movement away from the center region in a radial manner. An angle " θ ," which ranges from a zero point at "r" and increases in a clock-wise manner to "r'," defines an angular or rotational or tangential coordinate, which is the final coordinate defined on the present CMP apparatus. This coordinate system will be referenced throughout the present specification and most particularly below.

30

The CMP apparatus 100 includes a variety of features for polishing a surface of a workpiece, e.g., semiconductor wafer, substrate, glass, or a film of material such as a conductive film or a dielectric film on a workpiece. The conductive film can be crystalline, polycrystalline, or amorphous, and include materials such as silicon, polysilicon, amorphous silicon, copper, tungsten, aluminum, titanium, platinum,

35

5 silicides, polycides, alloys of these conductive materials, multilayered materials, and others. The dielectric layers include, among others, silicon dioxide, silicon nitride, doped and undoped oxides (e.g., borophosphosilicate ("BPSG") glass, phosphorus doped ("PSG") glass, fluorinated glass), tetraethylorthosilicate ("TEOS"), plastics, combinations thereof, and multilayered materials. The CMP apparatus 100 includes an
10 enclosed housing 103, which generally encases a processing area having at least three sections, but can include a variety of others. These sections include a polishing area 105, handler 107, and a wafer loading and unloading area 109, which are all described in more detail below.

15 The housing 103 is often made of removable panels disposed on a rigid frame structure. The removable panels enclose or encase the processing area, which tends to generate particulate contamination from the CMP process, including polishing pad and chemicals. The panels are removable for maintenance, safety reasons, and the like. Preferably, the panels are made of durable chemical resistant material, which can also
20 have insulating qualities to reduce the amount of noise generated from the processing area. In most embodiments, the panels include outer regions made of a plastic material (e.g., polyvinylchloride, polypropylene) or a light weight fiberglass material that is disposed against an insulating material to reduce noise originating from the processing area. The panels generally form a "box-like" structure supported by a frame to encase
25 the processing area. The frame is generally made of a strong and rigid material such as steel, stainless steel, and the like. Preferably, a chemical resistant coating (e.g., epoxy, chemical resistant paint, nickel plate, anodizing) is applied to the frame to protect the frame from chemicals in the processing area. The panels and doors also have exposed regions (e.g., clear glass, transparent plastic, etc.) for viewing or accessing the
30 processing area. Additional regions of the housing include openings to access the control panel and the like. Of course, the type of housing used depends highly upon the application.

The handler 107 includes two leaf structures 117, and 118 rotatably coupled to a
35 turret, which are also shown in Figure 1A. Figure 1A uses similar reference numerals

5 as Figure 1 for easy reading. The two leaf structures protrude outwardly in a radial direction from the turret 120 to access regions overlying each of the three polishing surfaces 111. Each of the leaf structures 117 and 118 include two fingers 119 and 121, each of which includes a carrier, device 123 attached to the end of the fingers 119 and 121. As shown, a preferred leaf structure includes at least two fingers 119 and 121
10 coupled or connected directly to each other, but is not limited to these two fingers. For example, other embodiments use a single finger to support a single carrier. Alternatively, other embodiments use more than two fingers such as three fingers, four fingers, five fingers, or more fingers, each having at least one carrier device attached thereto. Of course, the number of fingers on each leaf structure used depends upon the
15 application.

Each leaf structure rotates about the turret 120 in a relatively independent manner or a "scissors" like manner. In particular, leaf structure 117 rotates about the turret independently from leaf structure 118. To illustrate the concept of independent
20 movement among the two leaf structures, they can be defined as leaf structures 118 and leaf structure 117, which rotate independently from each other, depending upon the process or application. For example, the leaf structure 118 can rotate about the turret to move the workpiece to polishing surface 111(A) or to polishing surface 111(B), as shown in Figure 1, for example. Leaf structure 117 can also rotate from either
25 polishing surface 111(C) or polishing surface 111(B) to move the workpiece to the load/unload station 109 or pick up a workpiece from the load/unload station. Leaf structure 117 can rotate about the turret to the load/unload station, as well as rotate to one or more of the polishing surface(s). In reference to Figure 1A, for example, leaf structure 118 moves from a first position to a second position a shown by leaf structure
30 118(A), which includes fingers 119(A) and 121(A). Preferably, the leaf structures can not cross over each other to prevent a possibility of a collision between the two leaf structures. More preferably, each leaf structure can occupy any station, as long as another leaf structure is not occupying that station. Accordingly, each leaf structure has mechanical stops attached thereto to prevent collisions.

35

5 For instance, leaf structure 118 is aligned and is positioned with respect to leaf structure 117. As shown, leaf structure 118 includes stops 171 and 173. Leaf structure 118 rotates in a counter-clockwise manner about center region 129 and relative to leaf structure 117 until stop 173 comes in contact with stop 172, which is defined on leaf structure 117. Alternatively, leaf structure 118 rotates in a clockwise manner about
10 center region 129 and relative to leaf structure 117 until stop 171 comes in contact with stop 170, which is defined on leaf structure 117. Alternatively, leaf structure 118 rotates either in a clockwise or counter clockwise manner relative to leaf structure 117 until one of the stops collide with either stops 170 or 172. Leaf structure 118 also includes stops in the turret (or column) 120. For example, leaf structure 118 includes
15 stops 176, 177, and 178, which allow leaf structure 118 to stop a selected regions relative to the turret, but allow for greater than a 360 rotation about the center region 129. Additionally, the combination of leaf structures may also include a stop pin 180, which limits the movement of these structures relative to the internal drive gears.

20 Each leaf structure, including fingers, is made of a substantially rigid material to support at least one carrier device 123, but can support others. The leaf structure is often made of a high grade steel, stainless steel, or the like, which has a sufficient thickness to support the carrier device and withstand pressure as required by a variety of processes. A chemical resistant material or coating can be applied to the leaf structure
25 in preferred embodiments to withstand any aggressive chemicals, which may attack the leaf structure, from the processing area. Alternatively, the leaf structure can be made of an extremely high grade stainless steel (e.g., 303 or 304 stainless), which has been passivated (e.g., oxidized) to prevent chemical attack of the stainless steel material.

30 In operation, each leaf structure rotates horizontally about the turret along a fixed plane. Depending upon the application, rotation speed can vary. For example, each leaf structure can move in a constant, graduated, or stepped manner or rate around the turret and relative to each other. The rate is about 30 degrees per second ("DPS"). To transfer a workpiece from the load/unload station to a processing region overlying
35 the polishing surfaces, for example, the leaf structure moves at least 30 DPS, excluding

5 start-up or slow-down. During a polishing process, each leaf structure moves the carrier over the polishing surface at a rate ranging from about 0 DPS to about 10 DPS. These rates are often programmable. Additionally, the length of movement or "stroke" is also programmable. In most embodiments, each leaf structure accelerates to about 30 DPS in about 1/2 second, but can also accelerate at other rates. Additionally, each leaf
10 structure can also operate in a slow speed mode to a fast speed mode, with other speeds in between.

Each leaf structure attaches to an annular shaped member, 125 or 127, which can freely rotate about a center region 129 of the turret. The annular shaped member is
15 actually a bearing or bushing assembly and also supports the leaf structure about the turret in a rotatably coupled manner. The bearing or bushing assembly facilitates the rotational movement of the annular shaped member about the turret center region 129. Leaf structure 118 includes annular shaped region 127, and leaf structure 117 includes annular shaped region 125. An annular shaped gear or wheel drives each of the leaf
20 structures. Preferably, an independent gear or wheel is used to drive each of the leaf structures in an independent manner.

As shown, gear wheel 131 drives leaf structure 118 and gear wheel 133 drives leaf structure 117. Gear wheel 131 includes an outer gear periphery 143 and gear wheel
25 133 includes an outer gear periphery 141. To move the annular shaped member, each gear wheel or outer gear can intermesh into a gear or "ring" gear assembly 135 defined on the inner periphery of the annular shaped member to drive the annular shaped member in a rotational manner about the center 129 of the turret. Alternatively, the annular shaped gear or wheel includes an outer surface that is relatively smooth, but has
30 a large coefficient of friction relative to an inner periphery of the annular shaped member to drive the annular shaped member in a rotational manner about the center of the turret. This outer surface can be a "sticky" plastic material, rubber, or the like. As merely an example, the annular shaped gear or wheel is similar to "trucks" on a skateboard.

35

5 Each leaf structure includes a carrier device 123, which holds a workpiece to be polished on at least one of the polishing surfaces. A plurality of holes 145 are used to attach each carrier device to each leaf structure. Preferably, each carrier device is removable from the leaf structure by way of attachment member, e.g., bolts, screws, pins, etc. By way of such attachment member, each carrier device can be removed
10 and/or replaced for repair and preventive maintenance purposes. In some embodiments, one or more of the carrier devices is removed without interfering the operation of the other carrier devices.

15 The polishing area 105 has a plurality of polishing surfaces 111 (e.g., round wheels) disposed around handler or turret 120. Each of the polishing surfaces 111 generally includes a polishing pad 113 defined overlying a rotatable platen assembly 115. The polishing pad 113 is a disk-shaped object having the polishing surface 111, which is rotatable about a fixed plane and axis. In preferred embodiments, the disk-shaped object is rotatable at a constant and varying speeds. For example, the disk-shaped object rotates at a speed greater than about 200 revolutions per minute ("RPM"),
20 but less than about 2 RPM. Preferably, the speed of rotation ranges from about 10 RPM to about 150 RPM, but is often less than about 70 RPM. The disk-shaped object can accelerate to a speed of about 70 RPM in about 2 seconds or less, but can also be set at other acceleration rates. An electric motor often drives the disk-shaped object
25 about a fixed plane axis in the z-direction. The motor can drive the disk-shaped object directly or through a drive train, e.g., gears, belts. Preferably, the electric motor is a brush less servo motor made by Sierracin or Kollmorgen, but can also be others.

30 The polishing pad 113 is often made of a tough "fabric-like" chemical resistant material, which is often embedded with an abrasive material. The polishing pad can be made from a material such as a poly-urethane, polyester, acrylic, acrylic ester copolymers, poly tetra-fluoroethylene, polypropylene, polyethylene, poly 4-methyl pentene, cellulose, cellulose esters, polyamides such as nylon and aramids, polyimides, polyimideamide, polysiloxane, copolymers, polycarbonates, epoxides, phenolic resins,
35 and others. Of course, the type of material used depends upon the application. An

5 example of this polishing surface made of a poly-urethane material is a product sold by Rodel called IC-1000, but can be others. In most embodiments, the abrasive is a plurality of particles, which are selected from a material such as a borosilicate glass, titanium dioxide, titanium nitride, aluminum oxide, aluminum trioxide, iron nitrate, cerium oxide, silicon dioxide (colloidal silica), silicon nitride, silicon carbide, graphite,
10 diamond, and any mixtures thereof. The type of particle used depends highly upon the CMP application, e.g., tungsten, dielectric, oxide, nitride, etc. The abrasive is often mixed in a solution (e.g., water, acid, base, organic solvent, etc.) to form a slurry, which can be applied to the polishing pad in a manual or automated manner.

15 A simplified side-view diagram of the polishing area 105 is shown by way of Figure 2, for example. This diagram is merely an illustration and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize other modifications, alternatives, and variations. As shown, Figure 2 uses like reference numerals as the other Figures for easy reading. The polishing area 105 includes
20 polishing surface(s) 111, polishing pad(s) 113, and rotatable platen assembly 115. Each of the polishing pads includes an upper surface having the same or similar height relative to the z-axis. To rotate platen assembly 115, axle 203 drives the platen assembly by way of an attachment to a center region of the assembly. Axle 203 also inserts into annular region 201, which houses the axle. Axle 203 moves in or rotates in
25 annular region 201 by way of force applied to the axle by a drive assembly 205, which is defined below the rotatable platen assembly. Axle 203 drives or rotates the platen assembly in a constant, varying, or stepped manner. For example, platen assembly rotates at a speed ranging from about 2 RPM to about 200 RPM. Preferably, rotation occurs at a speed greater than about 30 RPM during processing, but also can be others.

30

In relation to the handler, including the leaf structure(s), a simplified side view diagram of the polishing area is shown by Figure 3. This diagram is merely an illustration and should not limit the scope of the claims herein. The diagram includes, among other features, the polishing area 105, and the polishing surfaces. As shown,
35 each of the polishing surfaces 111 is disposed around the handler, including the turret

5 120 and the leaf structure(s). Each leaf structure includes two fingers 119 and 121. These fingers were actually upper fingers. Additionally, each leaf structure includes lower fingers 301, which are directly below upper fingers 121. The leaf structure further includes lower fingers (not shown) directly below upper fingers 119. Between each pair of lower and upper finger is the carrier device 123. That is, each pair of
10 fingers holds the carrier device in parallel alignment to the polishing surface.

Each carrier device 123 includes an actuator or bellows device 307 between the fingers for adjusting the vertical or z-location of a workpiece held by a workpiece carrier (not shown) relative to the polishing surfaces. The bellows device has a range of
15 operation greater than about 3 1/2 inches or preferably greater than about 4 inches, which is measured from an upper point along the z-axis and a lower point along the z-axis. Bellows device 307 also provides force in the z-direction to the backside surface of the workpiece held by a workpiece carrier. In a specific embodiment, the force ranges from about 0 pounds to about 850 pounds and can be others. This force
20 provides a pressure of about 300 pounds and greater to, for example, an eight inch wafer, which is biased against the polishing surface.

The workpiece carrier is attached to the end of a rotatable spindle 303. Spindle 303 is defined in a z-direction in the carrier device and is held by at least the bellows
25 device. To drive the spindle in a rotational manner, spindle 303 is coupled to a drive assembly 311, which is driven by an electric motor (e.g., servo motor) 309. An example of this electric motor is a product manufactured by Animatics or Infranor, but can be others. A housing 305 encloses the spindle 303 and bellows 307 to protect them from the environment.

30

Figures 3A and 3B show simplified side-view and top-view diagrams, respectively, of handler according to an embodiment of the present invention. These Figures are merely illustrations and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize numerous variations, alternatives, and
35 modifications. Some like reference numerals are used in these Figures as the previous

5 Figures for easy cross-referencing. Additional numerals are used to describe selected details of the handler. As shown, the side-view diagram includes numerous features such as upper leaf structure 121 and lower leaf structure 301. One end of the leaf structures is operably coupled to turret 120. In most embodiments, the end coupled to the turret is relatively fixed to the turret and the distance between the ends of each leaf structure is fixed. In some embodiments, the two leaf structures can, however, move up and down along the z-axis by way of a driving device. Between each pair of lower and upper finger is the carrier device 123. That is, each pair of fingers holds the carrier device in parallel alignment to the polishing surface. Any up and down motion of the two leaf structures also moves the carrier device in a similar up and down manner.

15 The carrier device 123 includes an actuator or bellows device 307 between the fingers for adjusting the vertical or z-location of a workpiece held by a workpiece carrier (not shown) relative to the polishing surfaces. The bellows device has a range of operation greater than about 3 1/2 inches or preferably greater than about 4 inches, which is measured from an upper point along the z-axis and a lower point along the z-axis. Bellows device 307 also provides force or pressure in the z-direction to the backside surface of the workpiece held by a workpiece carrier. In a specific embodiment, the pressure applied by the bellows device ranges from about 0 pounds to about 850 pounds and can be others. In a specific embodiment, the force provides a pressure of about 300 pounds and greater to, for example, an eight inch wafer, which is biased against the polishing surface.

20 In a specific embodiment, each leaf structure includes a pivotable member, which tends to maintain parallel alignment between a workpiece surface and a polishing surface. Leaf structure 121 includes, among other elements, a pivotable member 321, which is connected by coupling 325. Pivotable member 321 pivots about coupling 325. Leaf structure 301 includes, among other elements, a pivotable member 323, which is connected by coupling 327. Pivotable member 323 pivots about coupling 327. Bellows device 307 is disposed between the pivotable members 321 and 323. Pivotable member 323 is connected to spindle 303 using coupling 331, and pivotable member

5 321 is connected to spindle 303 using coupling 329. Pivotal members work in tandem or pivot relative to the leaf structures about couplings 325 and 327. Pivotal members also work in tandem relative to spindle 303 about couplings 329 and 331.

10 Parallel alignment during processing of a workpiece occurs by way of a combination of pivotal members and couplings in connection to the spindle, among other elements. In particular, spindle 303 maintains a workpiece in parallel alignment to a polishing surface by way of a combination of movement from pivotal members about couplings 325 and 327 in some embodiments. In other embodiments, spindle 303 maintains a workpiece in parallel alignment to a polishing surface by way of a
15 combination of movement from pivotal members about couplings 329 and 331. Still further, a combination of movement about each of the couplings maintains a parallel alignment of a workpiece surface relative to a polishing surface. Such parallel alignment between a rotating workpiece surface and a rotating polishing surface is important for providing efficient and uniform polishing of films and the like on
20 substrates. To further understand the way these members work, it may be analogized that the combination of the pivotal members coupled to the spindle is similar in concept to "A-frame" support members, which secure a spindle for a wheel on an automobile. Similar to the wheel on the automobile on a road, which should be in parallel alignment to the road to maintain traction, the rotating workpiece surface is
25 maintained in parallel alignment to the rotating polishing surface to maintain uniform polishing characteristics.

Mechanical force or pressure is also placed on the carrier device to maintain force on upper leaf 121 or pivotal member 321 by way of actuator device 330, as
30 shown in Figure 3B. Actuator device 330 includes, among other elements, a pressure cylinder 331, which is coupled to a rigid or stationary location of upper leaf 121 by bracket or support 335, which can be secured to leaf 121 by welds, etc. Pressure cylinder 331 is coupled to the bracket by a pin or bolt, for example, which allows the pressure cylinder to move or pivot about a fixed axis. Movable end 331 of the actuator
35 assembly couples to a top surface of pivotal member 321 using a bracket 339, which

5 connects to or couples to the movable end 337 using a pin or bolt, which slides through an opening of the movable end 337. This movable end 337 can move or pivot about the pin or bolt during operation. Additionally, movable end 337 moves with pivotable member 321 and also adjusts or maintains a "pitch" of the pivotable member, thereby adjusting or maintaining the pitch of the assembly including the pivotable members,
10 spindle, and bellows device.

In a specific embodiment, operation of the carrier device works in the following manner. Spindle 303 rotates a workpiece, which is disposed against a surface of a rotating polishing pad. Pressure on a backside of the workpiece is placed using the
15 bellows device, which is coupled between the two pivotable members. To secure the relative position of the upper pivotable member, actuator device 330 applies force to the upper pivotable member using pressure cylinder, which is coupled to the upper surface of the upper pivotable member. Variations in the process can cause the relative position of the surface of the rotating workpiece with respect to the surface of the
20 rotating polishing surface to become out of alignment, e.g., non-parallel. These variations are absorbed using the pivotable members, which are coupled to each other using couplings.

In an alternative embodiment where the carrier device moves (randomly and)
25 upwardly outside of normal operating positions in the z-direction, the present invention includes an upper stop assembly 360 for the carrier device, as shown in the Figures 3A and 3B. The upper stop assembly includes a shock absorbing cylinder 341, which has a first end 347 that is pivotally attached using a pin, for example, to a portion of the upper leaf using a fixed mount 349 or bracket. The fixed mount can be secured to the upper
30 leaf by welds or bolts. Shock absorbing cylinder 341 also includes a second end, which is pivotally coupled to a first member 345, which is pivotally coupled to a second member 351 using coupling 343, which can be a pin or bolt. The second member 351 can be pivotally coupled to the pivotable member 321. A combination of these members, which are pivotally coupled to each other, translate vertical movement of the
35 spindle in the z-direction to shock absorbing cylinder. Shock absorbing cylinder

- 5 "absorbs" shocks from, for example, a sudden movement of the spindle in the z-direction in embodiments where the spindle moves outside a normal operating position.

In alternative embodiments, spindle has a lower stop position, which can be forcibly made using an internal carrier device. The low stop position selectively adjusts
10 the position of the carrier to a desired process location. In some embodiments, the low stop position is mechanically adjustable using simple tools or by hand. Alternatively, the low stop position is semi-automatically adjusted by way of computer software and the like. Of course, the adjustment of the lower stop depends upon the application.

15 The apparatus can be fully automatic or manual by way of at least the above handler which is coupled to a controller (not shown) and which can maintain parallel alignment between a substrate surface and a polishing surface over substantial variations in processing. A method according to the present invention may be briefly outlined as follows:

- 20
- (1) Provide plurality of workpieces to be processed in a workpiece carrier, e.g., boat or cassette;
 - (2) Transfer first workpiece (e.g., wafer having a film of tungsten, copper, aluminum, or dielectric material thereon) to an alignment station;
 - 25 (3) Align first workpiece;
 - (4) Transfer first workpiece onto a load/unload station;
 - (5) Position first workpiece on load/unload station to a first carrier of a first leaf structure;
 - (6) Pick-up first workpiece using the first carrier;
 - 30 (7) Position first workpiece for processing onto first processing surface, which is rotatable and maintain parallel alignment between the first workpiece and the first processing surface over process variations;
 - (8) Perform steps (1) to (6) for a second workpiece using a second carrier of a second leaf structure and then;

- 5 (9) Position second workpiece using second leaf structure for processing onto a second processing surface, which is rotatable and maintain parallel alignment between the first workpiece and the first processing surface over process variations;
- (10) Transfer first or second workpiece to load/unload station;
- 10 (11) Transfer second or first workpiece to load/unload station;
- (12) Transfer first workpiece into workpiece carrier using first leaf structure;
- (13) Transfer second workpiece into workpiece carrier or cassette using second leaf structure;
- (14) Perform remaining fabrication steps, as necessary.

15 The above sequence of steps are used to planarize a workpiece or planarize a film on a workpiece. These steps generally include the use of multiple carrier devices, which can each hold a workpiece for polishing, independently from each other. Accordingly, each carrier device can be adjusted independently to independently maintain processing conditions. Additionally, the multiple carrier devices can provide, for example, high

20 throughput and workpiece processing. Parallel alignment between a workpiece surface and the polishing surface is maintained using a novel handler. Again, these steps are merely examples and should not limit the scope of the claims herein. Details of the steps can be shown in a simplified flow diagram and the description below.

25 Figure 4 is a simplified flow diagram of a method 400 according to the present invention. This method is merely an example and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize other modifications, variations, and alternatives. The method generally describes a process of planarizing a tungsten film on a semiconductor wafer, for example.

30

 The method 400 begins by providing (step 401) a plurality of wafers having a film of tungsten thereon to be processed in a carrier, e.g., wafer boat. A first wafer is removed (step 403) by way of a pick-up arm from the carrier and placed on an alignment station, which aligns (step 405) the wafer flat to a desired position. The first

5 wafer is placed (step 407) on a load/unload station, which rotates to align the first wafer to a position to be picked up by a first carrier.

10 The first carrier rotates about the turret and positions its carrier head over the first wafer. The first carrier uses its bellows device to adjust the carrier head to a position directly overlying the wafer to pick up the wafer. Mechanical clamps secure the wafer to pick up (step 409) the wafer and vacuum secures the wafer to the carrier head. The bellows device adjusts the z-position of the wafer upwardly. The first carrier rotates about the turret to position (step 411) the wafer overlying a first polishing surface. The bellows device adjusts the z-position of the wafer downwardly such that 15 the face of the wafer is biased against the polishing surface to perform the polishing operation (step 413). The polishing surface is generally rotated by way of a drive mechanism to enhance the polishing action. Additionally, a spindle rotates the wafer in a circular manner to further enhance polishing in some embodiments.

20 In a specific embodiment, a slurry mixture is applied directly to the polishing surface to enhance removal of tungsten material. This slurry mixture can be transferred to the polishing pad by way of a metering pump, which is coupled to a slurry source. The slurry is often a solution containing an abrasive particle and oxidizer, e.g., H_2O_2 , KIO_3 , and ferric nitrate. The abrasive particle is often a borosilicate glass, titanium dioxide, titanium nitride, aluminum oxide, aluminum trioxide, iron nitrate, cerium 25 oxide, silicon dioxide (colloidal silica), silicon nitride, silicon carbide, graphite, diamond, and any mixtures thereof. In a tungsten process, a preferred abrasive particle is aluminum oxide. This particle is mixed in a solution of deionized water and oxidizer or the like. Preferably, the solution is also acidic.

30

Independent to the operation of the first carrier, a second carrier undergoes the following processing steps to perform chemical mechanical planarization of a second wafer. A second wafer is removed (step 415) by way of a pick-up arm from the carrier and is placed on an alignment station, which aligns (step 417) the wafer flat to a desired

5 position. The second wafer is placed (step 419) on a load/unload station, which rotates to align the second wafer to a position to be picked up by a second carrier.

10 The second carrier rotates about the turret and positions its carrier head over the second wafer. The second carrier uses its bellows to adjust the second carrier head to a position directly overlying the wafer to pick up the wafer. Mechanical clamps secure the wafer to pick up (step 421) the wafer, and vacuum secures the wafer to the carrier head. The bellows device adjusts the z-position of the wafer upwardly. The second carrier rotates about the turret to position (step 423) the wafer overlying a second polishing surface for polishing (step 425). The bellows device adjusts the z-position of
15 the wafer downwardly such that the face of the wafer is biased against the polishing surface. The polishing surface is generally rotated by way of a drive mechanism to enhance the polishing action. Additionally, a spindle rotates the wafer in a circular manner to further enhance polishing, if desired.

20 After the polishing operation of the first wafer is completed, the first wafer is transferred (step 427) to the load/unload station. In particular, the bellows device adjusts the z-location of the wafer upwardly away from the polishing surface. The turret rotates the first carrier to a region overlying the load/unload station. The bellows device adjusts the z-location downwardly toward the load/unload station. The vacuum
25 holding the wafer releases the wafer. The bellows device adjusts the carrier upwardly and the turret rotates the carrier away from the load/unload station so that the second wafer can be removed. Alternatively, the first carrier picks up another wafer to be processed and undergoes another polishing process.

30 The second wafer is also transferred (step 429) to the load/unload station after polishing is completed in an independent manner relative to the first wafer. In particular, the bellows device adjusts the z-location of the wafer upwardly away from the polishing surface. The turret rotates the second carrier to a region overlying the load/unload station. The bellows device adjusts the z-location downwardly toward the
35 load/unload station. The vacuum holding the wafer releases the wafer. The bellows

5 device adjusts the carrier upwardly and the turret rotates the carrier away from the load/unload station so that the first wafer can be removed, if necessary. Alternatively, the second carrier picks up another wafer to be processed and undergoes another polishing process. Of course, these sequences of steps are merely an illustration, which should not limit the scope of the claims herein.

10

In an alternative embodiment, the present invention provides a method, which may be briefly outlined as follows:

- (1) Provide plurality of workpieces to be processed in a workpiece carrier or boat;
- 15 (2) Transfer first workpiece (e.g., wafer having a film of tungsten, copper, aluminum, or dielectric material thereon) to an alignment station;
- (3) Align first workpiece;
- (4) Transfer first workpiece onto a load/unload station;
- (5) Transfer second workpiece (e.g., wafer having a film of tungsten, 20 copper, aluminum, or dielectric material thereon) to an alignment station;
- (6) Align second workpiece;
- (7) Transfer second workpiece onto a load/unload station;
- (8) Position first and second workpieces on load/unload station to a first 25 carrier and a second carrier, respectively, on a first leaf structure;
- (9) Pick-up first and second workpieces using the first carrier and the second carrier;
- (10) Position first and second workpieces for processing onto first processing 30 surface, which is rotatable, and maintain parallel alignment between the second workpiece and the first polishing surface;
- (11) Transfer polished first and second workpieces to load/unload station;
- (12) Transfer first (or second) workpiece into workpiece carrier;
- (13) Transfer second (or first) workpiece into workpiece carrier;
- (14) Perform remaining fabrication steps, as necessary.

5 The above sequence of steps are used to planarize at least two workpieces or planarize a film on two workpieces using a single leaf structure. While the first and second workpieces are being polished, a second leaf structure can begin processing third and fourth workpieces simultaneously. For example, the method can process third and fourth workpieces using the second leaf structure performing steps (2) - (10) above, while the first leaf structure is polishing the first and second workpieces. These steps generally include the use of at least two carrier devices, which can each hold a workpiece for polishing, on a single leaf structure, which can be processed independently from another leaf structure. Accordingly, at least two carrier devices can be adjusted independently to independently maintain processing conditions.

10

15 Additionally, the multiple carrier devices can provide, for example, high throughput of workpieces. Parallel alignment between the workpiece and the surface of the rotatable polishing surface is maintained using a novel handler. Again, these steps are merely examples and should not limit the scope of the claims herein. Details of the steps can be shown in a simplified flow diagram and the description below.

20

Figure 5 is a simplified flow diagram of a method 500 according to the present invention. This method is merely an example and should not limit the scope of the claims herein. One of ordinary skill in the art would recognize other modifications, variations, and alternatives. The method generally describes a process of planarizing a tungsten film on a semiconductor wafer, for example, by way of two carrier devices on a single leaf structure, such as the one described above, but can be others.

25

The method 500 begins by providing (step 501) a plurality of wafers having a film of tungsten thereon to be processed in a carrier, e.g., wafer boat. A first wafer is removed (step 503) by way of a pick-up arm from the carrier and placed on an alignment station, which aligns (step 505) the wafer flat to a desired position. The first wafer is placed (step 507) on a load/unload station, which rotates to align the first wafer to a position to be picked up by a first carrier on a first leaf structure.

30

5 These steps are repeated for processing a second wafer. For example, a second wafer is removed (step 509) by way of a pick-up arm from the carrier and placed on an alignment station, which aligns (step 511) the wafer flat to a desired position. The second wafer is placed (step 513) on a load/unload station, which rotates to align the second wafer to a position to be picked up by a second carrier on the first leaf structure,
10 which includes at least these two carrier devices.

 The first leaf structure including the carriers rotates about the turret and positions its carrier heads over the first and the second wafers. The first carrier uses its bellows device to adjust the carrier head to a position directly overlying the first wafer
15 to pick up the wafer. Mechanical clamps secure the first wafer to pick up (step 515) the first wafer and vacuum secures the wafer to the carrier head. The bellows device adjusts the z-position of the first wafer upwardly. Similarly, the second carrier head uses its bellows device to adjust the carrier head to a position directly overlying the second wafer to pick up the second wafer. Mechanical clamps secure the second wafer
20 to pick up (step 515) the wafer and vacuum secures the wafer to the carrier head. The bellows device adjusts the z-position of the second wafer upwardly.

 The first leaf structure including the carriers rotates about the turret to position the wafers overlying a first polishing surface. The bellows devices adjust the z-
25 positions of the wafers downwardly such that the faces of the wafers are biased against the polishing surface to perform the polishing operations (step 517). The polishing surface is generally rotated by way of a drive mechanism to enhance the polishing action. Additionally, a spindle rotates each of the wafers in a circular manner to further enhance polishing in some embodiments.

30 In a specific embodiment, a slurry mixture is applied directly to the polishing surface to enhance removal of tungsten material. This slurry mixture can be transferred to the polishing pad by way of a metering pump, which is coupled to a slurry source. The slurry is often a solution containing an abrasive particle and oxidizer, e.g., H_2O_2 ,
35 KIO_3 , and ferric nitrate. The abrasive particle is often a borosilicate glass, titanium

5 dioxide, titanium nitride, aluminum oxide, aluminum trioxide, iron nitrate, cerium oxide, silicon dioxide (colloidal silica), silicon nitride, silicon carbide, graphite, diamond, and any mixtures thereof. In a tungsten process, a preferred abrasive particle is aluminum oxide. This particle is mixed in a solution of deionized water and oxidizer or the like. Preferably, the solution is also acidic.

10

After the polishing operations of the first and second wafers are completed, the first and second wafers are transferred (step 519) to the load/unload station. In particular, the bellows devices adjust the z-locations of the wafers upwardly away from the polishing surface. The turret rotates the first leaf structure including the carriers to a region overlying the load/unload station. The bellows devices adjust the z-locations downwardly toward the load/unload station. Vacuum holding the wafers release the wafers. The bellows devices adjust the carriers upwardly again and the turret rotates the carriers away from the load/unload station. Next, the first or second wafer is placed on a transfer station (step 521).

20

Each wafer is then placed or transferred into a cassette holder (step 523). For example, the first wafer is picked up and placed in the cassette holder. The second wafer is then picked up and placed in the cassette holder. Alternatively, the second wafer is picked up and placed in the cassette holder. The first wafer is then picked up and placed in the cassette holder. As noted above, a second leaf structure coupled to the turret can pick up third and fourth wafers while the first and second wafers are being processed. The use of the first and second leaf structures including at least four carrier devices allows for parallel processing of at least two or four wafers at the same time. Subsequently, the first or second wafer is placed on the transfer station (step 525), which is then followed by placing the first or second wafer in cassette holder (step 527). Of course, these sequences of steps are merely illustrations and should not limit the scope of the claims herein.

Although the above description is described generally in terms of polishing a tungsten film on a wafer, it would be easily recognized that the invention has a broader

5 range of applicability. For example, the invention can also be applied to polishing surfaces of optical materials, substrates, glass, and other films on wafers. Additionally, the above method can be used for planarizing dielectric materials such as, for example, silicon dioxide, doped and undoped oxides, and other materials. Of course, the type of workpiece used depends highly upon the application.

10

15 In the above methods for polishing workpieces, parallel alignment between the workpiece surface and the polishing surface is maintained over process variations. In particular, parallel alignment during processing of a workpiece occurs by way of a combination of pivotable members and couplings in connection to the spindle, among other elements, such as those noted above, as well as others. As merely an example, a spindle such as the one described maintains a workpiece in parallel alignment to a polishing surface by way of a combination of movement from pivotable members about couplings in some embodiments. In other embodiments, spindle maintains a workpiece in parallel alignment to a polishing surface by way of a combination of movement from
20 pivotable members about couplings. Still further, a combination of movement about each of the couplings maintain a parallel alignment of a workpiece surface relative to a polishing surface. Such parallel alignment between a rotating workpiece surface and a rotating polishing surface is important for providing efficient and uniform polishing of films and the like on substrates. To further understand the way these members work, it
25 may be analogized that the combination of the pivotable members coupled to the spindle is similar in concept to "A-frame" support members, which secure a spindle for a wheel on an automobile. Similar to the wheel on the automobile on a road, which should be in parallel alignment to the road to maintain traction, the rotating workpiece surface is maintained in parallel alignment to the rotating polishing surface to maintain
30 uniform polishing characteristics. Of course, one of ordinary skill in the art would recognize other variations, modifications, and alternatives, which can be combined with any of the above embodiments, as well as others.

35 While the above is a full description of the specific embodiments, various modifications, alternative constructions and equivalents may be used. For example,

- 5 while the description above is in terms of a multi-carrier design using a single turret, it would be possible to implement the present invention with multiple turrets and even more carriers. Therefore, the above description and illustrations should not be taken as limiting the scope of the present invention which is defined by the appended claims.

What is claimed is:

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225